



CV-CFW103AL

Smart look Day/ Night Fixed Dome Camera with IR illuminator



Specifications

Parameter	CV-CFW103AL
Camera	
Image Sensor	1/3" 1.0 Mega Pixels CMOS
Effective Pixels	1280 (H) x 720 (V)
Min Illumination	0.05Lux/ F2.0, 0Lux IR on
Electronic Shutter	PAL : 1/25s~1/100,000s NTSC: 1/30s~1/100,000s
Video Frame Rate	PAL : 25fps NTSC: 30fps
Synchronization	Internal
Day & Night	Auto (ICR)/ Color/ B/W
Max IR Distance	30m
Digital Noise Reduction	2D
White Balance	Auto
AGC	Auto
BLC	Auto
Lens	
Focal Length	3.6 mm
Angular Field of View	H: 78° V: 42°
Lens Type	M12
Input / Output	
Video Output	1CH BNC HD-CVI video output
General	
Power	DC 12V±25%
Power Consumption	2.8W MAX
Working Temperature	-40°C~+60°C. Less than 90% RH (no condensation)
Dimensions	Φ93.4 mm × 79.7 mm
Weight (approx.)	280g
External Case	Metal

Key Features


- High-performance CMOS image sensor.
- Support 720p@25fps (PAL)/ 30fps (NTSC)
- Support 75-5 coaxial cable transmission up to 800m.
- High speed & long distance real-time transmission.
- Support ICR for day time and night time operation.
- Support auto exposure, auto white balance, auto electronic shutter and auto gain function.
- Support DC12V power supply.
- IP66 compliance.

Standard Accessories

- Quick guide.....1 pc
- Important safety instruction.....1 pc

*Refer to DVR spec sheet for recording frame rate limitation

Appearance



Important

- Safety Precaution: Carefully read the operating instruction manual before using this product.

- All pictures are simulated.
- Weights and dimensions are approximate.
- Specifications are subject to change without notice.
- These products may be subject to export control regulations.

DISTRIBUTED BY: